

If the rule is in BLACK text, then it is the same as 2017.

If the rule is in BLUE text, then it has been changed for 2018.

If any future revisions are made it will be in RED text.

Super Street

Class Designation: S/S

General Safety: All vehicles must conform with general IHRA safety rules.

Beam Tripper: A front beam tripper is permitted but can only extend 45° forward of the centerline of the front wheel.

Engine Coolant: Only water is permitted in the coolant system. Antifreeze or other additives are prohibited.

Fuel System: All cars must be equipped with a drain valve located on the return side of the fuel rail or regulator to facilitate the removal of fuel samples for fuel check purposes.

Hybrids: Import engines in Domestic bodies or Domestic engines in Import bodies are prohibited. All cars must be either Import bodied/powerd or Domestic bodied/powerd.

Crossover Rules: The crossover classes below run under their own set of class rules for their sanctioning body, and ignore the WCF Super Street rulebook totally. Every crossover car is 100% accountable for every rule in their rulebook, unless there is as an adjustment made in the table below. In some cases, a crossover class may need an adjustment to be slowed down or sped up to make parity with the WCF Super Street class.

Eligibility: Anyone can run under the crossover rules if you choose, even if you have not run the class before. However, if the car has ever competed in any of the classes below at that sanctioned event in the last two years then the car must run under the crossover rules, and will not be eligible to run under the WCF Super Street rulebook. If you have run more than one crossover class, then you may choose which crossover class that you want to run under. If there is any debate or question on the spirit of crossover eligibility, the event director/tech director will make the final decision on which rulebook the car must run under.

Body Component Exemption: In an effort to allow crossover cars to get to a lower minimum weight if the crossover rules allow you to run lighter than your normal weight, all crossover class racers can run any light weight body components even if your sanctioning body does not allow it.

Engine Containment Device: Engine diaper or catch pan device to capture oil and/or debris in the event of engine failure mandatory. If a catch pan device is used, catch pan must employ minimum 2-inch-high lips on all sides. Lips must be covered or curved inward, so as to contain oil in pan. Catch pan must cover entire area below the engine. Catch pan must extend from radiator support to firewall and from frame rail to frame rail. In all cases, lips must be adequate enough to contain oil in the catch pan. Should a competitor spill excessive oil from the catch pan and debris onto the track, he or she may be disqualified from further competition at the sole and absolute discretion of the event director.

Series	Class Name	Parity Adjustments
NMCA	N/A 10.5	<ul style="list-style-type: none"> All Cars: Add 150 lbs. All Cars: Wheelie bars must be removed
NMCA	Factory Super Car	<ul style="list-style-type: none"> All Cars: Deduct 50 lbs.
TX2K	Stick Shift Challenge	<ul style="list-style-type: none"> Domestic V8 Small Block Engines Only can crossover into Super Street with the following restrictions below. Any clutch assisted H-Pattern transmission permitted (No pneumatic or electronic assisted transmissions) H-Pattern Shifter required (No pneumatic or electronic assisted shifters) Stock Suspension Cars Only Maximum size slick or bias ply tire is 28.0" x 11.5". Any size DOT radial tire is permitted, except 315/60/15, 325/50/15, 295/55/15 or 295/60/15 Twin Turbos limited to: (Compressor Wheel 64.9mm Inducer / 86.9mm Exducer) (Turbine Wheel 74.9 Inducer / 66.9 Exducer) T4 only Minimum Weight: 3200 lbs. Fuel: Gasoline or any ethanol blended fuel is permitted. All fuels cannot exceed .799 specific gravity. Fuels will be checked with a digital specific gravity tester.